

Description

Ring part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS166273118
Minimum Qty (MOQ):	15 EA
NSN:	5325-01-090-9791
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS16627-3118 Specifications

Cross-sectional Shape Style:	Rectangular
Casehardening Indicator:	Not Casehardened
Outside Diameter:	1.273 Inches Minimum And 1.298 Inches Maximum
Major Thickness:	0.048 Inches Minimum And 0.052 Inches Maximum
Ring Style:	Internal Inverted Lugs
Usage Design:	Internal
Material Hardness Rating:	47.0 Rockwell C Minimum And 52.0 Rockwell C Maximum
Material:	Steel Fed Std 66 Aisi 1066 Or Steel Fed Std 66 Aisi 1069 Or Steel Fed Std 66 Aisi 1070 Or Steel Fed Std 66 Aisi 1072 Or Steel Fed Std 66 Aisi 1074 Or Steel Fed Std 66 Aisi 1075 Or Steel Fed Std 66 Aisi 1078 Or Steel Fed Std 66 Aisi 1080 Or Steel Fed Std 66 Aisi 1084 Or Steel Fed Std 66 Aisi 1086 Or Steel Fed Std 66 Aisi 1090
Material:	Steel Fed Std 66 Aisi 1066 Or Steel Fed Std 66 Aisi 1069 Or Steel Fed Std 66 Aisi 1070 Or Steel Fed Std 66 Aisi 1072 Or Steel Fed Std 66 Aisi 1074 Or Steel Fed Std 66 Aisi 1075 Or Steel Fed Std 66 Aisi 1078 Or Steel Fed Std 66 Aisi 1080 Or Steel Fed Std 66 Aisi 1084 Or Steel Fed Std 66 Aisi 1086 Or Steel Fed Std 66 Aisi 1090
Surface Treatment:	Phosphate Zinc
Surface Treatment Document And Classification:	Mil-p-16232, Type Z, Class 2 Mil Spec Single Treatment Response
Surface Treatment:	Phosphate, Mil-p-16232, Type Z, Class 2

How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16627-3118> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.