

## Description

For shaft size: 25/32", external bowed, cadmium plated steel, tapered section type, MS16628 series ring

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model: MS166281078

Minimum Qty (MOQ): 50

NSN: 5325-00-935-3787

Schedule B: 7318.29.0000

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi Sub 9



## P/N MS16628-1078 Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Inside Diameter:</b>	0.712 Inches Minimum And 0.727 Inches Maximum
<b>Casehardening Indicator:</b>	Not Casehardened
<b>Major Thickness:</b>	0.042 Inches Nominal
<b>Ring Style:</b>	External Bowed
<b>Usage Design:</b>	External
<b>Material Hardness Rating:</b>	66.0 Rockwell Superficial 30-n Minimum And 71.0 Rockwell Superficial 30-n Maximum
<b>End Play Takeup:</b>	0.020 Inches Maximum
<b>Material:</b>	Steel,fed Fed Std No. 66,aisi C1066 Thru C1090 Or Sae 1070 Thru 1090
<b>Material:</b>	Steel,fed Fed Std No. 66,aisi C1066 Thru C1090 Or Sae 1070 Thru 1090
<b>Surface Treatment:</b>	Cadmium And Chromate
<b>Surface Treatment:</b>	Cadmium And Chromate

## How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16628-1078> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.