

Description

For shaft size: 25/32", external bowed, cadmium plated steel, tapered section type, MS16628 series ring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS166281078
Minimum Qty (MOQ):	25
NSN:	5325-00-935-3787
Schedule B:	7318.29.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N MS16628-1078 Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	0.712 Inches Minimum And 0.727 Inches Maximum
Casehardening Indicator:	Not Casehardened
Major Thickness:	0.042 Inches Nominal
Ring Style:	External Bowed
Usage Design:	External
Material Hardness Rating:	66.0 Rockwell Superficial 30-n Minimum And 71.0 Rockwell Superficial 30-n Maximum
End Play Takeup:	0.020 Inches Maximum
Material:	Steel,fed Fed Std No. 66,aisi C1066 Thru C1090 Or Sae 1070 Thru 1090
Material:	Steel,fed Fed Std No. 66,aisi C1066 Thru C1090 Or Sae 1070 Thru 1090
Surface Treatment:	Cadmium And Chromate
Surface Treatment:	Cadmium And Chromate

How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16628-1078> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.