

Description

Retaining Ring part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS166281098
Minimum Qty (MOQ):	40 EA
NSN:	5325-01-066-9639
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS16628-1098 Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	0.900 Inches Minimum And 0.915 Inches Maximum
Casehardening Indicator:	Not Casehardened
Major Thickness:	0.040 Inches Minimum And 0.044 Inches Maximum
Ring Style:	External Bowed
Usage Design:	External
Material Hardness Rating:	66.0 Rockwell Superficial 30-n Minimum And 71.0 Rockwell Superficial 30-n Maximum
End Play Takeup:	0.021 Inches Minimum And 0.041 Inches Maximum
Material:	Steel Fed Std 66 Aisi 1066 Or Steel Fed Std 66 Aisi 1069 Or Steel Fed Std 66 Aisi 1070 Or Steel Fed Std 66 Aisi 1072 Or Steel Fed Std 66 Aisi 1074 Or Steel Fed Std 66 Aisi 1075 Or Steel Fed Std 66 Aisi 1078 Or Steel Fed Std 66 Aisi 1080 Or Steel Fed Std 66 Aisi 1084 Or Steel Fed Std 66 Aisi 1086 Or Steel Fed Std 66 Aisi 1090
Material:	Steel Fed Std 66 Aisi 1066 Or Steel Fed Std 66 Aisi 1069 Or Steel Fed Std 66 Aisi 1070 Or Steel Fed Std 66 Aisi 1072 Or Steel Fed Std 66 Aisi 1074 Or Steel Fed Std 66 Aisi 1075 Or Steel Fed Std 66 Aisi 1078 Or Steel Fed Std 66 Aisi 1080 Or Steel Fed Std 66 Aisi 1084 Or Steel Fed Std 66 Aisi 1086 Or Steel Fed Std 66 Aisi 1090
Surface Treatment:	Cadmium And Chromate
Surface Treatment:	Cadmium, Qq-p-416, Type 2, Class 3

How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16628-1098> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.