

Description

Retaining Ring part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS166284027
Minimum Qty (MOQ):	25 EA
NSN:	5325-01-047-0619
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS16628-4027 Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	0.245 Inches Minimum And 0.252 Inches Maximum
Casehardening Indicator:	Not Casehardened
Major Thickness:	0.023 Inches Minimum And 0.027 Inches Maximum
Ring Style:	External Bowed
Usage Design:	External
Material Hardness Rating:	63.0 Rockwell Superficial 30-n Minimum And 69.5 Rockwell Superficial 30-n Maximum
End Play Takeup:	0.041 Inches Minimum And 0.053 Inches Maximum
Material:	Steel, Ams 5520
Material:	Steel Comp 632
Material Document And Classification:	Ams 5520 Assn Std Single Material Response
Surface Treatment:	Passivate
Surface Treatment:	Passivated, Qq-p-35

How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16628-4027> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.