

Description

Ring part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS166284050
Minimum Qty (MOQ):	10 EA
NSN:	5325-00-598-0861
Schedule B:	7318.16.0060
ECCN:	9A991
National Motor Freight:	063520, Waveguide In Boxes / Crates



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS16628-4050 Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	0.461 Inches Nominal
Casehardening Indicator:	Not Casehardened
Major Thickness:	0.035 Inches Nominal
Ring Style:	External Bowed
Usage Design:	External
Material Hardness Rating:	63.0 Rockwell Superficial 30-n Minimum And 69.5 Rockwell Superficial 30-n Maximum
End Play Takeup:	0.020 Inches Maximum
Material:	Steel, Corrosion Resisting
Material:	Steel Corrosion Resisting
Surface Treatment:	Passivate
Surface Treatment:	Passivated

How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16628-4050> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.