

Description

Retaining Ring part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------|
| SKU / Model: | MS166291025 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5325-01-126-1353 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



* See page 2 for technical characteristics

P/N MS16629-1025 Specifications

| | |
|---|---|
| Cross-sectional Shape Style: | Rectangular |
| Casehardening Indicator: | Not Casehardened |
| Outside Diameter: | 0.270 Inches Minimum And 0.290 Inches Maximum |
| Major Thickness: | 0.013 Inches Minimum And 0.017 Inches Maximum |
| Ring Style: | Internal Bowed |
| Usage Design: | Internal |
| Material Hardness Rating: | 86.0 Rockwell Superficial 15-n Minimum And 88.0 Rockwell Superficial 15-n Maximum |
| End Play Takeup: | 0.030 Inches Minimum And 0.042 Inches Maximum |
| Material: | Steel,fed Std 66,comp 1066,1069,1070,1071,1072,1074,1075,1078,1080,1084,1085,1086,or 1090 |
| Material: | Steel,fed Std 66,comp 1066,1069,1070,1071,1072,1074,1075,1078,1080,1084,1085,1086,or 1090 |
| Surface Treatment: | Cadmium And Chromate |
| Surface Treatment Document And Classification: | Qq-p-416, Type 2, Class 3 Fed Spec Single Treatment Response |
| Surface Treatment: | Cadmium, Qq-p-416, Type 2, Class 3 |

How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16629-1025> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.