

Description

Retaining Ring part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS166291025
Minimum Qty (MOQ):	50
NSN:	5325-01-126-1353
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N MS16629-1025 Specifications

Cross-sectional Shape Style:	Rectangular
Casehardening Indicator:	Not Casehardened
Outside Diameter:	0.270 Inches Minimum And 0.290 Inches Maximum
Major Thickness:	0.013 Inches Minimum And 0.017 Inches Maximum
Ring Style:	Internal Bowed
Usage Design:	Internal
Material Hardness Rating:	86.0 Rockwell Superficial 15-n Minimum And 88.0 Rockwell Superficial 15-n Maximum
End Play Takeup:	0.030 Inches Minimum And 0.042 Inches Maximum
Material:	Steel,fed Std 66,comp 1066,1069,1070,1071,1072,1074,1075,1078,1080,1084,1085,1086,or 1090
Material:	Steel,fed Std 66,comp 1066,1069,1070,1071,1072,1074,1075,1078,1080,1084,1085,1086,or 1090
Surface Treatment:	Cadmium And Chromate
Surface Treatment Document And Classification:	Qq-p-416, Type 2, Class 3 Fed Spec Single Treatment Response
Surface Treatment:	Cadmium, Qq-p-416, Type 2, Class 3

How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16629-1025> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.