

Description

Ring part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS166291031
Minimum Qty (MOQ):	40 EA
NSN:	5325-00-598-4267
National Motor Freight:	063520, Waveguide In Boxes / Crates



NO IMAGE
AVAILABLE

P/N MS16629-1031 Specifications

Cross-sectional Shape Style:	Rectangular
Casehardening Indicator:	Not Casehardened
Outside Diameter:	0.346 Inches Nominal
Major Thickness:	0.015 Inches Nominal
Ring Style:	Internal Bowed
Usage Design:	Internal
Material Hardness Rating:	86.0 Rockwell Superficial 15-n Minimum And 88.0 Rockwell Superficial 15-n Maximum
Strength Rating:	253000.0 Pounds Per Square Inch Minimum Tensile
End Play Takeup:	0.021 Inches Maximum
Material:	Steel,fed,fed Std No. 66,aisi C1066 Thru C1090 Or Sae 1070 Thru 1090
Material:	Steel,fed,fed Std No. 66,aisi C1066 Thru C1090 Or Sae 1070 Thru 1090
Surface Treatment:	Cadmium And Chromate
Surface Treatment:	Cadmium Plated W/chromate Treatment Finish

How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16629-1031> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.