

**Description**

Ring part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS166291031
Minimum Qty (MOQ):	40 EA
NSN:	5325-00-598-4267
National Motor Freight:	063520, Waveguide In Boxes / Crates

NO IMAGE  
AVAILABLE

## P/N MS16629-1031 Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Casehardening Indicator:</b>	Not Casehardened
<b>Outside Diameter:</b>	0.346 Inches Nominal
<b>Major Thickness:</b>	0.015 Inches Nominal
<b>Ring Style:</b>	Internal Bowed
<b>Usage Design:</b>	Internal
<b>Material Hardness Rating:</b>	86.0 Rockwell Superficial 15-n Minimum And 88.0 Rockwell Superficial 15-n Maximum
<b>Strength Rating:</b>	253000.0 Pounds Per Square Inch Minimum Tensile
<b>End Play Takeup:</b>	0.021 Inches Maximum
<b>Material:</b>	Steel,fed,fed Std No. 66,aisi C1066 Thru C1090 Or Sae 1070 Thru 1090
<b>Material:</b>	Steel,fed,fed Std No. 66,aisi C1066 Thru C1090 Or Sae 1070 Thru 1090
<b>Surface Treatment:</b>	Cadmium And Chromate
<b>Surface Treatment:</b>	Cadmium Plated W/chromate Treatment Finish

## How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16629-1031> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.