

Description

Ring part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS166291037
Minimum Qty (MOQ):	10 EA
NSN:	5325-00-200-7246
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

P/N MS16629-1037 Specifications

Cross-sectional Shape Style:	Rectangular
Casehardening Indicator:	Not Casehardened
Outside Diameter:	0.415 Inches Nominal
Major Thickness:	0.025 Inches Nominal
Ring Style:	Internal Bowed
Usage Design:	Internal
Material Hardness Rating:	69.5 Rockwell Superficial 30-n Minimum And 73.0 Rockwell Superficial 30-n Maximum
Strength Rating:	253000.000 Pounds Per Square Inch Minimum Tensile
End Play Takeup:	0.022 Inches Maximum
Material:	Steel,fed Std No. 66,aisi C1066 Thru C1090 Or Sae 1070 Thru 1090
Material:	Steel,fed Std No. 66,aisi C1066 Thru C1090 Or Sae 1070 Thru 1090
Surface Treatment:	Cadmium And Chromate
Surface Treatment:	Cadmium And Chromate

How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16629-1037> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.