

Description

Ring part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS166294056
Minimum Qty (MOQ):	10 EA
NSN:	5325-01-099-8150
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

P/N MS16629-4056 Specifications

Cross-sectional Shape Style:	Rectangular
Casehardening Indicator:	Not Casehardened
Outside Diameter:	0.610 Inches Minimum And 0.630 Inches Maximum
Major Thickness:	0.033 Inches Minimum And 0.037 Inches Maximum
Ring Style:	Internal Bowed
Usage Design:	Internal
Material Hardness Rating:	63.0 Rockwell Superficial 30-n Minimum And 69.5 Rockwell Superficial 30-n Maximum
End Play Takeup:	0.019 Inches Minimum And 0.037 Inches Maximum
Material:	Steel, Ams 5520 Or Steel A1s1 632
Material:	Steel Comp 632 Or Steel A1s1 632
Material Document And Classification:	Ams 5520 Assn Std 1st Material Response

How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16629-4056> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.