

**Description**

Ring part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                             |
|-------------------------|-----------------------------|
| SKU / Model:            | MS166294062                 |
| Minimum Qty (MOQ):      | 20 EA                       |
| NSN:                    | 5325-00-285-6702            |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |

NO IMAGE  
AVAILABLE

## P/N MS16629-4062 Specifications

|  |   |
|--|---|
| <b>Cross-sectional Shape Style:</b>          | Rectangular   |
| <b>Casehardening Indicator:</b>              | Not Casehardened  |
| <b>Outside Diameter:</b>                     | 0.694 Inches Nominal  |
| <b>Major Thickness:</b>                      | 0.035 Inches Nominal  |
| <b>Ring Style:</b>                           | Internal Bowed  |
| <b>Usage Design:</b>                         | Internal  |
| <b>Material Hardness Rating:</b>             | 63.0 Rockwell Superficial 30-n Minimum And 69.5 Rockwell Superficial 30-n Maximum |
| <b>End Play Takeup:</b>                      | 0.011 Inches Maximum  |
| <b>Material:</b>                             | Steel, Ams 5520   |
| <b>Material:</b>                             | Steel Comp 632  |
| <b>Material Document And Classification:</b> | Ams 5520 Assn Std Single Material Response  |
| <b>Surface Treatment:</b>                    | Passivate   |
| <b>Surface Treatment:</b>                    | Passivated, Qq-p-35   |

## How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16629-4062> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.