

## P/N MS16631-3185

### **Description**

MS16631 series ring

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS166313185

Minimum Qty (MOQ): 10

NSN: 5325-00-226-9985

Schedule B: 7318.15.5030

ECCN: 9A991

National Motor Freight: 095190, Hardware, Noi Sub 9



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS16631-3185 Specifications

Cross-sectional Shape Style:	Beveled One Outside Corner
Casehardening Indicator:	Not Casehardened
Outside Diameter:	1.985 Inches Minimum And 2.018 Inches Maximum
Minor Thickness:	0.045 Inches Minimum And 0.047 Inches Maximum
Major Thickness:	0.059 Inches Minimum And 0.065 Inches Maximum
Ring Style:	Internal
Usage Design:	Internal
Material Hardness Rating:	47.0 Rockwell C Minimum And 52.0 Rockwell C Maximum
Material:	Steel,fed 66,1066 To 1090
Material:	Steel,fed 66,1066 To 1090
Surface Treatment:	Phosphate
Surface Treatment:	Phosphate Coated

# **How to Order**

Order this retaining ring from our inventory online by visiting <a href="https://military-fasteners.com/rings/retaining+rings/MS16631-3185">https://military-fasteners.com/rings/retaining+rings/MS16631-3185</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rings/retaining+rings/MS16631-3185">https://military-fasteners.com/rings/retaining+rings/MS16631-3185</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rings/retaining+rings/MS16631-3185">https://military-fasteners.com/rings/retaining+rings/MS16631-3185</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rings/retaining+rings/MS16631-3185">https://military-fasteners.com/rings/retaining+rings/MS16631-3185</a> and selecting the quantity you want of the property of the propert