

Description

Ring part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-----------------------------|
| SKU / Model: | MS166321040 |
| Minimum Qty (MOQ): | 30 EA |
| NSN: | 5325-00-174-8695 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |

NO IMAGE
AVAILABLE

P/N MS16632-1040 Specifications

| | |
|-------------------------------------|---|
| Cross-sectional Shape Style: | Rectangular |
| Inside Diameter: | 0.354 Inches Minimum And 0.362 Inches Maximum |
| Casehardening Indicator: | Not Casehardened |
| Major Thickness: | 0.023 Inches Minimum And 0.207 Inches Maximum |
| Ring Style: | C |
| Usage Design: | External |
| Material Hardness Rating: | 67.5 Rockwell Superficial 30-n Minimum And 72.0 Rockwell Superficial 30-n Maximum |
| Material: | Steel,fed Std 66 Composition 1066 Thru 1090 |
| Material: | Steel,fed Std 66 Composition 1066 Thru 1090 |
| Surface Treatment: | Cadmium And Phosphate |
| Surface Treatment: | Cadmium Plated Finish, Qq-p-416a, Type 2, Class 3 |

How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16632-1040> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.