

Description

Ring part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS166333018
Minimum Qty (MOQ):	20 EA
NSN:	5325-00-282-2426
National Motor Freight:	063520, Waveguide In Boxes / Crates

NO IMAGE
AVAILABLE

P/N MS16633-3018 Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	0.142 Inches Minimum And 0.146 Inches Maximum
Casehardening Indicator:	Not Casehardened
Major Thickness:	0.023 Inches Minimum And 0.027 Inches Maximum
Ring Style:	E
Usage Design:	External
Material Hardness Rating:	65.5 Rockwell Superficial 30-n Minimum And 71.0 Rockwell Superficial 30-n Maximum
Material:	Steel,fed,fed Std 66,fs 1066 To Fs 1090
Material:	Steel,fed,fed Std 66,fs 1066 To Fs 1090
Surface Treatment:	Phosphate
Surface Treatment:	Phosphate Coated

How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16633-3018> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.