

Description

Retaining Ring part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------|
| SKU / Model: | MS166334014 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5325-00-808-0350 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



* See page 2 for technical characteristics

P/N MS16633-4014 Specifications

| | |
|--|---|
| Cross-sectional Shape Style: | Rectangular |
| Inside Diameter: | 0.099 Inches Minimum And 0.103 Inches Maximum |
| Casehardening Indicator: | Not Casehardened |
| Major Thickness: | 0.023 Inches Minimum And 0.027 Inches Maximum |
| Ring Style: | E |
| Usage Design: | External |
| Material Hardness Rating: | 63.0 Rockwell Superficial 30-n Minimum And 69.5 Rockwell Superficial 30-n Maximum |
| Material: | Steel, Ams 5520 |
| Material: | Steel Comp 632 |
| Material Document And Classification: | Ams 5520 Assn Std Single Material Response |
| Surface Treatment: | Passivate |
| Surface Treatment: | Passivated, Qq-p-35 |
| Nondefinitive Spec/std Data: | 1 Type And 5 Class |

How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16633-4014> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.