

Description

MS16633 series ring

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS166334025
Minimum Qty (MOQ):	100
NSN:	5325-00-205-6552
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N MS16633-4025 Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	0.204 Inches Minimum And 0.208 Inches Maximum
Casehardening Indicator:	Not Casehardened
Major Thickness:	0.023 Inches Minimum And 0.027 Inches Maximum
Ring Style:	E
End Item Identification:	W/s:support Equipment, B-52 Aircraft; Torpedo, Mk 48; Central Message Switch, An/tyc-39a; Communications Terminal, An/ugc-74; Missile, Air-to-air, Sparrow (aim-7); Missile, Advanced Medium Range Air-to-air (amraam)/aim120a; Support Equipment, B-1 Aircraft; Communications Terminal; Aircraft, (c-130h, Mc-130h, Ec-130e, Hc-130)
Usage Design:	External
Material Hardness Rating:	63.0 Rockwell Superficial 30-n Minimum And 69.5 Rockwell Superficial 30-n Maximum
Material:	Steel, Ams 5520
Material:	Steel Comp 632
Material Document And Classification:	Ams 5520 Assn Std Single Material Response
Surface Treatment:	Passivate
Surface Treatment:	Passivated, Qq-p-35
Nondefinitive Spec/std Data:	1 Type And 5 Class

How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16633-4025> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.