

Description

Ring part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS166344037
Minimum Qty (MOQ):	25 EA
NSN:	5325-00-850-9719
Schedule B:	7318.16.0060
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N MS16634-4037 Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	0.300 Inches Nominal
Casehardening Indicator:	Not Casehardened
Major Thickness:	0.035 Inches Nominal
Ring Style:	E Bowed
Usage Design:	External
Material Hardness Rating:	44.0 Rockwell C Minimum And 51.0 Rockwell C Maximum
End Play Takeup:	0.025 Nominal Centimeters
Material:	Steel, Ams 5520
Material:	Steel Comp 632
Material Document And Classification:	Ams 5520 Assn Std Single Material Response
Surface Treatment:	Passivate
Surface Treatment:	Passivated, Qq-p-35

How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16634-4037> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.