

**Description**

thread: 2-56, length: 13/64in., head width: 5/64in., thread length: 9/64in., 80,000 psi tensile strength

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[NAS1352C02-3](#) [NAS1352C023](#)

SKU / Model:	MS169951
Minimum Qty (MOQ):	100
NSN:	5305-00-068-5409
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS16995-1 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.116 Inches Minimum And 0.148 Inches Maximum
<b>Fastener Length:</b>	0.172 Inches Minimum And 0.204 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.134 Inches Minimum And 0.140 Inches Maximum
<b>Head Height:</b>	0.083 Inches Minimum And 0.086 Inches Maximum
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.086 Inches
<b>Width Across Flats:</b>	0.078 Inches Minimum And 0.079 Inches Maximum
<b>Thread Quantity Per Inch:</b>	56
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Hardness Rating:</b>	80.0 Rockwell B Minimum Overall
<b>Minimum Yield Strength:</b>	30000 Pounds Per Square Inch
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	66 Fed Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this socket head cap screws from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS16995-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.