

Description

thread: 2-56, length: 13/64in., head width: 5/64in., thread length: 9/64in., 80,000 psi tensile strength

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[NAS1352C02-3](#) [NAS1352C023](#)

SKU / Model:	MS169951
Minimum Qty (MOQ):	100
NSN:	5305-00-068-5409
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS16995-1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.116 Inches Minimum And 0.148 Inches Maximum
Fastener Length:	0.172 Inches Minimum And 0.204 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.134 Inches Minimum And 0.140 Inches Maximum
Head Height:	0.083 Inches Minimum And 0.086 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.086 Inches
Width Across Flats:	0.078 Inches Minimum And 0.079 Inches Maximum
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this socket head cap screws from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS16995-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.