

P/N MS16995-100

Description

Fastener Length: 2-1/2", Thread: 1/2-13, Head Width: 3/8", Thread Length: 1-63/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS16995100
Minimum Qty (MOQ):	1
NSN:	5305-00-226-7609
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS16995-100 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.690 Inches Minimum And 2.135 Inches Maximum
Fastener Length:	2.440 Inches Minimum And 2.500 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.735 Inches Minimum And 0.750 Inches Maximum
Head Height:	0.492 Inches Minimum And 0.500 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.500 Inches
Width Across Flats:	0.375 Inches Minimum And 0.379 Inches Maximum
Thread Quantity Per Inch:	13
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	6 Туре

How to Order

Order this socket head cap screws from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/MS16995-100 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.