

Description

length: 1/2", thread: 4-40, hex socket head, corrosion resistant steel, MS16995 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[NAS1352C04-8](#)

| | |
|-------------------------|---|
| SKU / Model: | MS1699511 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5305-00-068-5414 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS16995-11 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.420 Inches Minimum And 0.500 Inches Maximum |
| Fastener Length: | 0.470 Inches Minimum And 0.500 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.176 Inches Minimum And 0.183 Inches Maximum |
| Head Height: | 0.108 Inches Minimum And 0.112 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.112 Inches |
| Width Across Flats: | 0.094 Inches Minimum And 0.095 Inches Maximum |
| Thread Quantity Per Inch: | 40 |
| Minimum Tensile Strength: | 80000 Pounds Per Square Inch |
| Hardness Rating: | 80.0 Rockwell B Minimum Overall |
| Minimum Yield Strength: | 30000 Pounds Per Square Inch |
| Material: | Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 6 Type |

How to Order

Order this socket head cap screws from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS16995-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.