

Description

MS16995-13 Socket Head Cap Screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS1699513
Minimum Qty (MOQ):	50
NSN:	5305-01-472-3735
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NO IMAGE
AVAILABLE

P/N MS16995-13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Nominal
Fastener Length:	0.750 Inches Nominal
Head Style:	Knurled No. 1
Head Diameter:	0.134 Inches Minimum And 0.140 Inches Maximum
Head Height:	0.083 Inches Minimum And 0.086 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.112 Inches
Width Across Flats:	0.0781 Inches Minimum And 0.0791 Inches Maximum
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	480000 Pounds Per Square Inch
Minimum Yield Strength:	30000 Pounds Per Square Inch
Special Features:	Head Style Manufacturers Option Plain Or Knurled
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	St0304 Mfr Ref 1st Material Response Overall And St0080 Mfr Ref 2nd Material Response Overall And St0305 Mfr Ref 3rd Material Response Overall And St0316 Mfr Ref 4th Material Response Overall And St0082 Mfr Ref 5th Material Response Overall Or St0430 Mfr Ref All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec 1st Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS16995-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.