

## P/N MS16995-16B

### **Description**

Fastener Length: 1/4", Thread: 6-32, Head Width: 7/64", Thread Length: 1/4",

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS1699516B

Minimum Qty (MOQ): 10

NSN: 5305-00-499-4959

Schedule B: 7318.15.2091

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)











<sup>\*</sup> See page 2 for technical characteristics

# P/N MS16995-16B Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.158 Inches Minimum And 0.250 Inches Maximum
Fastener Length:	0.220 Inches Minimum And 0.250 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.218 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.134 Inches Minimum And 0.138 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.109 Inches Minimum And 0.111 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Special Features:	Finish Color Black
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Oxide Overall
Surface Treatment Document And Classification:	Mil-c-13924,cl 4 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	6 Type

## **How to Order**

Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/MS16995-16B">https://military-fasteners.com/screws/socket+head+cap+screws/MS16995-16B</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.