

Description

Fastener Length: 3/8", Thread: 6-32, Head Width: 7/64", Thread Length: 3/8", MS16995 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS1699517B
Minimum Qty (MOQ):	50
NSN:	5305-00-230-2058
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS16995-17B Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.283 Inches Minimum And 0.375 Inches Maximum
Fastener Length:	0.345 Inches Minimum And 0.375 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.218 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.134 Inches Minimum And 0.138 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.109 Inches Minimum And 0.111 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Special Features:	Finish Color Black
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Oxide Overall
Surface Treatment Document And Classification:	Mil-c-13924,cl 4 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	6 Type

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS16995-17B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.