

**Description**

Fastener Length: 39/64", Thread: 6-32, Head Width: 7/64", Thread Length: 35/64",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS1699519B
Minimum Qty (MOQ):	20
NSN:	5305-00-256-7282
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS16995-19B Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.533 Inches Minimum And 0.625 Inches Maximum
<b>Fastener Length:</b>	0.595 Inches Minimum And 0.625 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.218 Inches Minimum And 0.226 Inches Maximum
<b>Head Height:</b>	0.134 Inches Minimum And 0.138 Inches Maximum
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Width Across Flats:</b>	0.109 Inches Minimum And 0.111 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Hardness Rating:</b>	80.0 Rockwell B Minimum Overall
<b>Minimum Yield Strength:</b>	30000 Pounds Per Square Inch
<b>Special Features:</b>	Finish Color Black
<b>Material:</b>	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses Overall
<b>Surface Treatment:</b>	Oxide Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-13924,cl 4 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc
<b>Nondefinitive Spec/std Data:</b>	6 Type

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS16995-19B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.