

P/N MS16995-26

Description

length: 1/2", thread: 8-32, hexagon, socket head, corrosion resistant steel, MS16995 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

NAS1352C08-8

SKU / Model: MS1699526

Minimum Qty (MOQ): 100


NSN: 5305-00-988-7602

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS16995-26 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.408 Inches Minimum And 0.500 Inches Maximum
Fastener Length:	0.470 Inches Minimum And 0.500 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.158 Inches Minimum And 0.164 Inches Maximum
Internal Drive Style:	Hexagon
End Item Identification:	Mrap Rg-33 And Rg-33 Auv
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.140 Inches Minimum And 0.142 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316 Or Steel Comp 384 Or Steel Comp Xm-7 Overall
Material Document And Classification:	Astm A493 Assn Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/MS16995-26 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outher to complete your order.