

P/N MS16995-26

Military-Fasteners.com

Description

length: 1/2", thread: 8-32, hexagon, socket head, corrosion resistant steel, MS16995 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

NAS1352C08-8

SKU / Model:	MS1699526
Minimum Qty (MOQ):	100
NSN:	5305-00-988-7602
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS16995-26 Specifications

Thread Direction:Right-handThread Jirection:Right-handFastener Length:0.408 Inches Minimum And 0.500 Inches MaximumFastener Length:0.470 Inches Minimum And 0.500 Inches MaximumHead Style:Flat ChamferHead Diameter:0.262 Inches Minimum And 0.270 Inches MaximumHead Height:0.158 Inches Minimum And 0.164 Inches MaximumInternal Drive Style:HexagonEnd Item Identification:Mrap Rg-33 And Rg-33 AuvNominal Thread Diameter:0.164 Inches0.164 Inches0.140 Inches Minimum And 0.142 Inches MaximumWidth Across Flats:0.140 Inches Minimum And 0.142 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:80000 Pounds Per Square InchMaterial Document And Classification:Astm A493 Assn Std All Material Response OverallSurface Treatment:Passivate OverallSurface Treatment Document AndQrp-35 Fed Spec Single Treatment Response Overall		
Thread Length:0.408 Inches Minimum And 0.500 Inches MaximumFastener Length:0.470 Inches Minimum And 0.500 Inches MaximumHead Style:Flat ChamferHead Diameter:0.262 Inches Minimum And 0.270 Inches MaximumHead Height:0.158 Inches Minimum And 0.164 Inches MaximumInternal Drive Style:HexagonEnd Item Identification:Mrap Rg-33 And Rg-33 AuvNominal Thread Diameter:0.164 Inches0.164 Inches0.140 Inches Minimum And 0.142 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:80000 Pounds Per square InchMaterialSteel Comp 302 Or Steel Comp 303 Or Steel Comp 305 Or Steel Comp 316 Or Steel Comp 384 Or Steel Comp 384 Or Steel Comp 305 Or St	Thread Class:	3a
Fastener Length:0.470 Inches Minimum And 0.500 Inches MaximumHead Style:Flat ChamferHead Diameter:0.262 Inches Minimum And 0.270 Inches MaximumHead Height:0.158 Inches Minimum And 0.164 Inches MaximumInternal Drive Style:HexagonEnd Item Identification:Mrap Rg-33 And Rg-33 AuvNominal Thread Diameter:0.164 Inches0.164 InchesMinimum And 0.142 Inches MaximumWidth Across Flats:0.140 Inches Minimum And 0.142 Inches MaximumThread Quantity Per Inch:32Material:Steel Comp 302 Or Steel Comp 303 Or Steel Comp 305 Or Steel Comp 316 Or Steel Comp 384 Or SteelMaterial Document And Classification:Astm A493 Assn Std All Material Response OverallSurface Treatment:Pasivate OverallSurface Treatment And Classification:Qr-p35 Fed Spiel Freatment Response Overall	Thread Direction:	Right-hand
Head Style:Flat ChamferHead Diameter:0.262 Inches Minimum And 0.270 Inches MaximumHead Height:0.158 Inches Minimum And 0.164 Inches MaximumInternal Drive Style:HexagonEnd Item Identification:Mrap Rg-33 And Rg-33 AuvNominal Thread Diameter:0.164 InchesVidth Across Flats:0.140 Inches Minimum And 0.142 Inches MaximumThread Quantity Per Inch:32Material:0.000 Pounds Per Square InchMaterial:Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316 Or Steel Comp 384 Or SteelMaterial Document And Classification:Astm A493 Assm Std All Material Response OverallSurface Treatment:Passivate OverallQ-p-35 Fed Spec Single Treatment Response Overall	Thread Length:	0.408 Inches Minimum And 0.500 Inches Maximum
Head Diameter:0.262 Inches Minimum And 0.270 Inches MaximumHead Height:0.158 Inches Minimum And 0.164 Inches MaximumInternal Drive Style:HexagonEnd Item Identification:Mrap Rg-33 And Rg-33 AuvNominal Thread Diameter:0.164 InchesVidth Across Flats:0.140 Inches Minimum And 0.142 Inches MaximumThread Quantity Per Inch:32Material:80000 Pounds Per Square InchMaterial:Steel Comp 302 Or Steel Comp 303 Or Steel Comp 305 Or Steel Comp 316 Or Steel Comp 384 Or SteelMaterial:Steel Comp 302 Or Steel Comp 303 Or Steel Comp 305 Or Steel Comp 316 Or Steel Comp 384 Or SteelSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Astm A493 Assn Std All Material Response OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Open Space Single Treatment Response Overall	Fastener Length:	0.470 Inches Minimum And 0.500 Inches Maximum
Head Height:0.158 Inches Minimum And 0.164 Inches MaximumInternal Drive Style:HexagonEnd Item Identification:Mrap Rg-33 And Rg-33 AuvNominal Thread Diameter:0.164 InchesVidth Across Flats:0.140 Inches Minimum And 0.142 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:80000 Pounds Per Square InchMaterial:Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316 Or Steel Comp 384 Or SteelMaterial Document And Classification:Astm A493 Assn Std All Material Responses OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Qep-35 Fed Spec Single Treatment Response Overall	Head Style:	Flat Chamfer
Internal Drive Style:HexagonEnd Item Identification:Mrap Rg-33 And Rg-33 AuvNominal Thread Diameter:0.164 Inches0.164 Inches0.164 InchesWith Across Flats:0.140 Inches Minimum And 0.142 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:0.000 Pounds Per Square InchMaterial:Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316 Or Steel Comp 384 Or SteelMaterial Document And Classification:Astm A493 Assn Std All Material Responses OverallSurface Treatment:Pasivate OverallSurface Treatment Document And Classification:Qu-p-35 Fed Spec Single Treatment Response Overall	Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
End Item Identification:Mrap Rg-33 And Rg-33 AuvNominal Thread Diameter:0.164 InchesWidth Across Flats:0.140 Inches Minimum And 0.142 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:80000 Pounds Per Square InchMaterial:Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316 Or Steel Comp 384 Or SteelMaterial Document And Classification:Astm A493 Assn Std All Material Responses OverallSurface Treatment:Passivate OverallQuartication:Quartication:Quartication:Quartication:Passivate Overall	Head Height:	0.158 Inches Minimum And 0.164 Inches Maximum
Nominal Thread Diameter:0.164 InchesWidth Across Flats:0.140 Inches Minimum And 0.142 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:80000 Pounds Per Square InchMaterial:Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316 Or Steel Comp 384 Or SteelMaterial Document And Classification:Astm A493 Assn Std All Material Responses OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Qq-p-35 Fed Spec Single Treatment Response Overall	Internal Drive Style:	Hexagon
Width Across Flats:0.140 Inches Minimum And 0.142 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:80000 Pounds Per Square InchMaterial:Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316 Or Steel Comp 384 Or SteelMaterial Document And Classification:Astm A493 Assn Std All Material Responses OverallSurface Treatment:Passivate OverallQuartity Per Inch:Q-p-35 Fed Spec Single Treatment Response Overall	End Item Identification:	Mrap Rg-33 And Rg-33 Auv
Thread Quantity Per Inch:32Minimum Tensile Strength:80000 Pounds Per Square InchMaterial:Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316 Or Steel Comp 384 Or SteelMaterial Document And Classification:Astm A493 Assn Std All Material Responses OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Q-p-35 Fed Spec Single Treatment Response Overall	Nominal Thread Diameter:	0.164 Inches
Minimum Tensile Strength:80000 Pounds Per Square InchMaterial:Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316 Or Steel Comp 384 Or Steel Comp Xm-7 OverallMaterial Document And Classification:Astm A493 Assn Std All Material Responses OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Qq-p-35 Fed Spec Single Treatment Response Overall	Width Across Flats:	0.140 Inches Minimum And 0.142 Inches Maximum
Material:Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316 Or Steel Comp 384 Or Steel Comp Xm-7 OverallMaterial Document And Classification:Astm A493 Assn Std All Material Responses OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Qq-p-35 Fed Spec Single Treatment Response Overall	Thread Quantity Per Inch:	32
Material:Comp Xm-7 OverallMaterial Document And Classification:Astm A493 Assn Std All Material Responses OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Qq-p-35 Fed Spec Single Treatment Response Overall	Minimum Tensile Strength:	80000 Pounds Per Square Inch
Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall	Material:	
Surface Treatment Document And Qq-p-35 Fed Spec Single Treatment Response Overall Classification: Qq-p-35 Fed Spec Single Treatment Response Overall	Material Document And Classification:	Astm A493 Assn Std All Material Responses Overall
Classification: Qq-p-35 Fed Spec Single Treatment Response Overall	Surface Treatment:	Passivate Overall
Thread Series Designator: Unc		Qq-p-35 Fed Spec Single Treatment Response Overall
	Thread Series Designator:	Unc

How to Order

Order this socket head cap screw from our inventory online by visiting <u>https://military-fasteners.com/screws/socket+head+cap+screws/MS16995-26</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.