

P/N MS16995-29

Description

Fastener Length: 7/8", Thread: 8-32, Head Width: 9/64", Thread Length: 1/4",

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS1699529

Minimum Qty (MOQ): 50

NSN: 5305-00-988-7605

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N MS16995-29 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.250 Inches Nominal
Fastener Length:	0.875 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.625 Inches Nominal
Head Height:	0.162 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.141 Inches Minimum And 0.143 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Minimum Yield Strength:	30000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Screw, Captive
Special Features:	Pernasm16995
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Astm F 593 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Aa-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS16995-29 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.