

P/N MS16995-48B

Description

Fastener Length: 33/64", Thread: 1/4-20, Head Width: 3/16", Thread Length: 33/64",

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS1699548B

Minimum Qty (MOQ): 5

NSN: 5305-00-421-7915

Schedule B: 7318.15.2091

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS16995-48B Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.384 Inches Minimum And 0.516 Inches Maximum
Fastener Length:	0.484 Inches Minimum And 0.516 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.365 Inches Minimum And 0.375 Inches Maximum
Head Height:	0.244 Inches Minimum And 0.250 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.188 Inches Minimum And 0.190 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	6 Type

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/MS16995-48B and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/socket+head+cap+screws/MS16995-48B and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/socket+head+cap+screws/MS16995-48B and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/ms16995-48B and selecting the property of the