

P/N MS16995-50B

Description

Fastener Length: 3/4", Thread: 1/4-20, Head Width: 3/16", Thread Length: 3/4",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS1699550B

Minimum Qty (MOQ):

NSN: 5305-00-421-7914

Schedule B: 7318.15.2091

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS16995-50B Specifications

Thread Direction: Right-hand O.620 Inches Minimum And 0.750 Inches Maximum O.720 Inches Minimum And 0.750 Inches Maximum Fastener Length: O.720 Inches Minimum And 0.750 Inches Maximum Head Style: Flat Chamfer Head Diameter: O.365 Inches Minimum And 0.375 Inches Maximum Head Height: O.244 Inches Minimum And 0.375 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: O.250 Inches Width Across Flats: O.188 Inches Minimum And 0.190 Inches Maximum Thread Quantity Per Inch: O.8000 Pounds Per Square Inch Hardness Rating: Minimum Tensile Strength: Minimum Yield Strength: Steel Comp 300 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 305 Overall Or Steel Comp 310 Overall Material: Overall Material Document And Classification: Surface Treatment: Oxide Overall Surface Treatment Document And Classification: Thread Series Designator: Unc Nondefinitive Spec/std Data: 6 Type	Thread Class:	3a
Thread Length: 0.620 Inches Minimum And 0.750 Inches Maximum 7 Sastener Length: 0.720 Inches Minimum And 0.750 Inches Maximum Flead Style: Flat Chamfer Flat Chamfer 1 0.365 Inches Minimum And 0.375 Inches Maximum 1 Nead Height: 0.244 Inches Minimum And 0.250 Inches Maximum 1 Internal Drive Style: Hexagon Nominal Thread Diameter: 0.250 Inches Width Across Flats: 0.188 Inches Minimum And 0.190 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Surface Treatment: Oxide Overall Surface Treatment Document And Classification: Thread Series Designator: Unc		
Fastener Length: 0.720 Inches Minimum And 0.750 Inches Maximum Head Style: Flat Chamfer Head Diameter: 0.365 Inches Minimum And 0.375 Inches Maximum Head Height: 0.244 Inches Minimum And 0.250 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.250 Inches Width Across Flats: 0.188 Inches Minimum And 0.190 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: 0xide Overall Surface Treatment Document And Classification: Inc		Right-hand
Head Style: Head Diameter: O.365 Inches Minimum And 0.375 Inches Maximum Head Height: O.244 Inches Minimum And 0.250 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: O.250 Inches Width Across Flats: O.188 Inches Minimum And 0.190 Inches Maximum Thread Quantity Per Inch: O.20 Minimum Tensile Strength: B0000 Pounds Per Square Inch Hardness Rating: B0.0 Rockwell B Minimum Overall Minimum Yield Strength: Suel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: Oxide Overall Surface Treatment Document And Classification: Thread Series Designator: Unc	Thread Length:	0.620 Inches Minimum And 0.750 Inches Maximum
Head Diameter: 0.365 Inches Minimum And 0.375 Inches Maximum 1nternal Drive Style: Nominal Thread Diameter: 0.250 Inches Width Across Flats: 0.188 Inches Minimum And 0.190 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: Manderial: Minimum Yield Strength: 30000 Pounds Per Square Inch Material: Material Document And Classification: Surface Treatment: Oxide Overall Surface Treatment Document And Classification: Thread Series Designator: Unc 0.365 Inches Minimum And 0.375 Inches Maximum 0.244 Inches Maximum 0.250 Inches Maximum 0.250 Inches Maximum And 0.190 Inches Maximum 0.190 Inches Ma	Fastener Length:	0.720 Inches Minimum And 0.750 Inches Maximum
Head Height: 0.244 Inches Minimum And 0.250 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.250 Inches Width Across Flats: 0.188 Inches Minimum And 0.190 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Oxide Overall Surface Treatment Document And Classification: Mil-c-13924,cl 4 Mil Spec Single Treatment Response Overall Thread Series Designator: Unc	Head Style:	Flat Chamfer
Internal Drive Style: Hexagon Nominal Thread Diameter: 0.250 Inches Width Across Flats: 0.188 Inches Minimum And 0.190 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Oxide Overall Mil-c-13924,cl 4 Mil Spec Single Treatment Response Overall Thread Series Designator: Unc	Head Diameter:	0.365 Inches Minimum And 0.375 Inches Maximum
Nominal Thread Diameter:0.250 InchesWidth Across Flats:0.188 Inches Minimum And 0.190 Inches MaximumThread Quantity Per Inch:20Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:80.0 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 OverallMaterial Document And Classification:66 Fed Std All Material Responses OverallSurface Treatment:Oxide OverallSurface Treatment Document And Classification:Mil-c-13924,cl 4 Mil Spec Single Treatment Response OverallThread Series Designator:Unc	Head Height:	0.244 Inches Minimum And 0.250 Inches Maximum
Width Across Flats: 0.188 Inches Minimum And 0.190 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Oxide Overall Mil-c-13924,cl 4 Mil Spec Single Treatment Response Overall Thread Series Designator: Unc	Internal Drive Style:	Hexagon
Thread Quantity Per Inch: Minimum Tensile Strength: Hardness Rating: Minimum Yield Strength: Material: Material: Material Document And Classification: Surface Treatment: Surface Treatment Document And Classification: Thread Series Designator: Ounce Document And Classification: Thread Series Designator: Document And Classification: Document And Classi	Nominal Thread Diameter:	0.250 Inches
Minimum Tensile Strength: Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Oxide Overall Surface Treatment Document And Classification: Mil-c-13924,cl 4 Mil Spec Single Treatment Response Overall Thread Series Designator: Unc	Width Across Flats:	0.188 Inches Minimum And 0.190 Inches Maximum
Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Oxide Overall Surface Treatment Document And Classification: Mil-c-13924,cl 4 Mil Spec Single Treatment Response Overall Thread Series Designator: Unc	Thread Quantity Per Inch:	20
Minimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 OverallMaterial Document And Classification:66 Fed Std All Material Responses OverallSurface Treatment:Oxide OverallSurface Treatment Document And Classification:Mil-c-13924,cl 4 Mil Spec Single Treatment Response OverallThread Series Designator:Unc	Minimum Tensile Strength:	80000 Pounds Per Square Inch
Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: Surface Treatment: Oxide Overall Mil-c-13924,cl 4 Mil Spec Single Treatment Response Overall Thread Series Designator: Unc	Hardness Rating:	80.0 Rockwell B Minimum Overall
Material: Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Oxide Overall Surface Treatment Document And Classification: Mil-c-13924,cl 4 Mil Spec Single Treatment Response Overall Thread Series Designator: Unc	Minimum Yield Strength:	30000 Pounds Per Square Inch
Surface Treatment: Surface Treatment Document And Classification: Thread Series Designator: Oxide Overall Mil-c-13924,cl 4 Mil Spec Single Treatment Response Overall Unc	Material:	
Surface Treatment Document And Classification: Thread Series Designator: Mil-c-13924,cl 4 Mil Spec Single Treatment Response Overall Unc	Material Document And Classification:	66 Fed Std All Material Responses Overall
Classification: Mil-c-13924,cl 4 Mil Spec Single Treatment Response Overall Thread Series Designator: Unc	Surface Treatment:	Oxide Overall
		Mil-c-13924,cl 4 Mil Spec Single Treatment Response Overall
Nondefinitive Spec/std Data: 6 Type	Thread Series Designator:	Unc
	Nondefinitive Spec/std Data:	6 Type

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/MS16995-50B and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.