

P/N MS16995-65

Description

MS16995-65, Socket Head Cap Screw, flat head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS1699565

Minimum Qty (MOQ): 10

NSN: 5305-00-988-7839

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS16995-65 Specifications

Thread Direction: Right-hand Thread Length: 0.734 Inches Minimum And 0.875 Inches Maximum Fastener Length: 0.845 Inches Minimum And 0.875 Inches Maximum Head Style: Flat Chamfer Head Diameter: 0.457 Inches Minimum And 0.469 Inches Maximum Head Height: 0.306 Inches Minimum And 0.313 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.312 Inches Width Across Flats: 0.250 Inches Minimum And 0.253 Inches Maximum Thread Quantity Per Inch: 18 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.00 Rockwell B Minimum Overall Minimum Yield Strength: 3000 Pounds Per Square Inch Hardness Rating: 80.00 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: 9asivate Overall Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall Thread Series Designator: Unc Nondefinitive Spec/std Data: 6 Type	Thread Class:	3a
Thread Length: O.345 Inches Minimum And 0.875 Inches Maximum Fastener Length: O.845 Inches Minimum And 0.875 Inches Maximum Head Style: Head Diameter: O.457 Inches Minimum And 0.469 Inches Maximum Head Height: O.306 Inches Minimum And 0.313 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: O.312 Inches Width Across Flats: O.250 Inches Minimum And 0.253 Inches Maximum Thread Quantity Per Inch: I8 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Overall Material Document And Classification: Surface Treatment: Surface Treatment Document And Classification: Thread Series Designator: Unc		
Fastener Length: 0.845 Inches Minimum And 0.875 Inches Maximum Head Style: Flat Chamfer Head Diameter: 0.457 Inches Minimum And 0.469 Inches Maximum Head Height: 0.306 Inches Minimum And 0.313 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.312 Inches Width Across Flats: 0.250 Inches Minimum And 0.253 Inches Maximum Thread Quantity Per Inch: 18 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Q-p-35 Fed Spec Single Treatment Response Overall Thread Series Designator: Unc		Right-hand
Head Style: Head Diameter: 0.457 Inches Minimum And 0.469 Inches Maximum Head Height: 0.306 Inches Minimum And 0.313 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.312 Inches Width Across Flats: 0.250 Inches Minimum And 0.253 Inches Maximum Thread Quantity Per Inch: 18 Minimum Tensile Strength: B0000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: 0000 Pounds Per Square Inch Material: 0000 Pounds Per Square Inch Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Unc	Thread Length:	0.734 Inches Minimum And 0.875 Inches Maximum
Head Diameter: Head Height: 0.306 Inches Minimum And 0.313 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.312 Inches Width Across Flats: 0.250 Inches Minimum And 0.253 Inches Maximum Thread Quantity Per Inch: Hardness Rating: Minimum Tensile Strength: Monour Yield Strength: 3000 Pounds Per Square Inch Material: Material: Material Document And Classification: Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Thread Series Designator: Unc	Fastener Length:	0.845 Inches Minimum And 0.875 Inches Maximum
Head Height: 0.306 Inches Minimum And 0.313 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.312 Inches Width Across Flats: 0.250 Inches Minimum And 0.253 Inches Maximum Thread Quantity Per Inch: 18 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Unc	Head Style:	Flat Chamfer
Internal Drive Style: Hexagon Nominal Thread Diameter: 0.312 Inches Width Across Flats: 0.250 Inches Minimum And 0.253 Inches Maximum Thread Quantity Per Inch: 18 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: 0q-p-35 Fed Spec Single Treatment Response Overall Thread Series Designator: Unc	Head Diameter:	0.457 Inches Minimum And 0.469 Inches Maximum
Nominal Thread Diameter: 0.312 Inches Width Across Flats: 0.250 Inches Minimum And 0.253 Inches Maximum Thread Quantity Per Inch: 18 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Unc	Head Height:	0.306 Inches Minimum And 0.313 Inches Maximum
Width Across Flats: 0.250 Inches Minimum And 0.253 Inches Maximum Thread Quantity Per Inch: 18 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Surface Treatment Document And Classification: Thread Series Designator: Unc	Internal Drive Style:	Hexagon
Thread Quantity Per Inch: Minimum Tensile Strength: Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Qq-p-35 Fed Spec Single Treatment Response Overall Thread Series Designator: Unc	Nominal Thread Diameter:	0.312 Inches
Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:80.0 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 OverallMaterial Document And Classification:66 Fed Std All Material Responses OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Qq-p-35 Fed Spec Single Treatment Response OverallThread Series Designator:Unc	Width Across Flats:	0.250 Inches Minimum And 0.253 Inches Maximum
Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall Thread Series Designator: Unc	Thread Quantity Per Inch:	18
Minimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 OverallMaterial Document And Classification:66 Fed Std All Material Responses OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Qq-p-35 Fed Spec Single Treatment Response OverallThread Series Designator:Unc	Minimum Tensile Strength:	80000 Pounds Per Square Inch
Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Classification: Thread Series Designator: Unc	Hardness Rating:	80.0 Rockwell B Minimum Overall
Material: Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall Thread Series Designator: Unc	Minimum Yield Strength:	30000 Pounds Per Square Inch
Surface Treatment: Surface Treatment Document And Classification: Thread Series Designator: Passivate Overall Qq-p-35 Fed Spec Single Treatment Response Overall Unc	Material:	
Surface Treatment Document And Classification: Thread Series Designator: Unc	Material Document And Classification:	66 Fed Std All Material Responses Overall
Classification: Classification: Classification: Classification: Classification: Classification: Classification: Unc	Surface Treatment:	Passivate Overall
		Qq-p-35 Fed Spec Single Treatment Response Overall
Nondefinitive Spec/std Data: 6 Type	Thread Series Designator:	Unc
	Nondefinitive Spec/std Data:	6 Type

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/MS16995-65 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.