

Description

Fastener Length: 1-3/4", Thread: 3/8-16, Head Width: 5/16", Thread Length: 1-9/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS1699584
Minimum Qty (MOQ):	2
NSN:	5305-00-226-7238
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS16995-84 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.210 Inches Minimum And 1.563 Inches Maximum
Fastener Length:	1.710 Inches Minimum And 1.750 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.550 Inches Minimum And 0.563 Inches Maximum
Head Height:	0.368 Inches Minimum And 0.375 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.375 Inches
Width Across Flats:	0.312 Inches Minimum And 0.316 Inches Maximum
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	6 Type

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS16995-84> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.