

P/N MS16995-9

Description

Thread Qty: 40, Material: Steel, Surface Treatment: Passivate, Tensile Strength: 80000, Head Style: Flat Chamfer, Drive Style: Hexagon, MS16995 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

NAS1352C044 NAS1352C04-4

SKU / Model:	MS169959
Minimum Qty (MOQ):	100

NSN: 5305-00-068-5276

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS16995-9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.170 Inches Minimum And 0.250 Inches Maximum
Fastener Length:	0.220 Inches Minimum And 0.250 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.176 Inches Minimum And 0.183 Inches Maximum
Head Height:	0.108 Inches Minimum And 0.112 Inches Maximum
Internal Drive Style:	Hexagon
End Item Identification:	W/s: Communications Terminal, An/ugc-74; Communications Terminal, Satellite An/gsc-39(v)1; Traffic Jam, An/tlq-17a; Support Equipment, B-52 Aircraft; Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Close In Weapon System (ciws-phalanx); Missile, Advanced Medium Range Air-to-air (amraam)/aim120a; Aircraft, Airlifter C-17a; Trainer, B-1b Aircraft; Support Equipment, B-1 Aircraft
Nominal Thread Diameter:	0.112 Inches
Width Across Flats:	0.094 Inches Minimum And 0.095 Inches Maximum
Thread Quantity Per Inch: 40	
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	6 Type

How to Order

