

Description

Fastener Length: 49/64", Thread: 1/2-13, Head Width: 3/8", Thread Length: 39/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS1699592
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-226-7607
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS16995-92 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.590 Inches Minimum And 0.612 Inches Maximum
Fastener Length:	0.744 Inches Minimum And 0.766 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.735 Inches Minimum And 0.750 Inches Maximum
Head Height:	0.492 Inches Minimum And 0.500 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.500 Inches
Width Across Flats:	0.375 Inches Minimum And 0.379 Inches Maximum
Thread Quantity Per Inch:	13
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS16995-92> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.