

Description

Fastener Length: 2-", Thread: 1/2-13, Head Width: 3/8", Thread Length: 1-55/64", MS16995 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS1699598 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5305-00-962-8617 |
| Schedule B: | 7318.15.2091 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS16995-98 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.862 Inches Minimum |
| Fastener Length: | 2.000 Inches Nominal |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.735 Inches Minimum And 0.750 Inches Maximum |
| Head Height: | 0.492 Inches Minimum And 0.500 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.500 Inches |
| Width Across Flats: | 0.375 Inches Minimum And 0.379 Inches Maximum |
| Thread Quantity Per Inch: | 13 |
| Minimum Tensile Strength: | 80000 Pounds Per Square Inch |
| Hardness Rating: | 80.0 Rockwell B Minimum Overall |
| Minimum Yield Strength: | 30000 Pounds Per Square Inch |
| Material: | Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS16995-98> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.