

P/N MS16996-14B

Military-Fasteners.com

Description

MS16996-14B Socket Head Cap Screw

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | MS1699614B |
|-------------------------|---|
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-373-2599 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS16996-14B Specifications

| Thread Class: | За |
|---|--|
| Thread Direction: | Right-hand |
| Thread Length: | 1.000 Inches Maximum |
| Fastener Length: | 0.970 Inches Minimum And 1.000 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.303 Inches Minimum And 0.313 Inches Maximum |
| Head Height: | 0.185 Inches Minimum And 0.190 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.190 Inches |
| Width Across Flats: | 0.1562 Inches Minimum And 0.1587 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 80000 Pounds Per Square Inch |
| Hardness Rating: | 80.0 Rockwell B Minimum Overall |
| Minimum Yield Strength: | 30000 Pounds Per Square Inch |
| Material: | Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp Xm-7 Overall |
| Material Document And Classification: | Astm A493 Assn Std All Material Responses Overall |
| Surface Treatment: | Passivate Overall And Oxide Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec 1st Treatment Response Overall And Mil-c-13924 Cl 4 Mil Spec 2nd Treatment Response Overall |
| Thread Series Designator: | Unf |
| | |

How to Order

Order this socket head cap screw from our inventory online by visiting <u>https://military-fasteners.com/screws/socket+head+cap+screws/MS16996-14B</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.