

P/N MS16996-3

Description

Fastener Length: 15/64", Thread: 0-80, Head Width: 3/64", Thread Length: 13/64", MS16996 series screw

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

Alternate Part Numbers

NAS1351C004 NAS1351C00-4

SKU / Model: MS169963

Minimum Qty (MOQ): 100

NSN: 5305-00-959-1910

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS16996-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.195 Inches Minimum And 0.250 Inches Maximum
Fastener Length:	0.220 Inches Minimum And 0.250 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.091 Inches Minimum And 0.096 Inches Maximum
Head Height:	0.057 Inches Minimum And 0.060 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.060 Inches
Width Across Flats:	0.050 Inches Minimum And 0.051 Inches Maximum
Thread Quantity Per Inch:	80
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	6 Type

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS16996-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.