

Description

Fastener Length: 1-1/64", Thread: 5/16-24, Head Width: 1/4", Thread Length: 15/16", MS16996 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS1699632
Minimum Qty (MOQ):	10
NSN:	5305-00-225-9443
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS16996-32 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.933 Inches Minimum
Fastener Length:	1.000 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.457 Inches Minimum And 0.469 Inches Maximum
Head Height:	0.306 Inches Minimum And 0.313 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.312 Inches
Width Across Flats:	0.250 Inches Minimum And 0.253 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS16996-32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.