

Description

MS16996-4 SOCKET HEAD CAP SCREW

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS169964
Minimum Qty (MOQ):	100
NSN:	5305-00-057-9972
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS16996-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.375 Inches Maximum
Fastener Length:	0.366 Inches Minimum And 0.375 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.091 Inches Minimum And 0.096 Inches Maximum
Head Height:	0.057 Inches Minimum And 0.060 Inches Maximum
Internal Drive Style:	Hexagon
End Item Identification:	W/s:low Altitude Navigation & Targeting Infrared System (Iantirn); Helicopter, Carrier Based Asw, Sh-60f; Missile, Advanced Medium Range Air-to-air (amraam)/aim120a; Support Equipment, B-1 Aircraft; Aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130); Helicopter, Observation (ahip), Oh-58d; Missile, Air-to-air, Amraam; Support Equipment, B-52 Aircraft; Teletype, Model 28
Nominal Thread Diameter:	0.060 Inches
Width Across Flats:	0.050 Inches Minimum And 0.051 Inches Maximum
Thread Quantity Per Inch:	80
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS16996-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.