

Description


Fastener Length: 3/8", Thread: 6-32, Head Width: 7/64", Thread Length: 3/8" ,

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS1699719L
Minimum Qty (MOQ):	50
NSN:	5305-01-269-2597
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	156600, Plastic / Rubber Article Viz:



* See page 2 for technical characteristics

P/N MS16997-19L Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.280 Inches Minimum And 0.375 Inches Maximum
Fastener Length:	0.342 Inches Minimum And 0.375 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.218 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.134 Inches Minimum And 0.138 Inches Maximum
Locking Feature:	Patch Threads Or Strip Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.109 Inches Minimum And 0.111 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Fastener And 45.0 Rockwell C Maximum Fastener
Material:	Plastic Locking Feature
Material:	Steel Fastener
Material Document And Classification:	Mil-f-18240 Mil Spec Single Material Response Locking Feature
Surface Treatment:	Cadmium Fastener And Chromate Fastener
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Fastener
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	4 Type

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS16997-19L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.