

**Description**


Fastener Length: 3/8", Thread: 6-32, Head Width: 7/64", Thread Length: 3/8" ,

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS1699719L
Minimum Qty (MOQ):	50
NSN:	5305-01-269-2597
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	156600, Plastic / Rubber Article Viz:



\* See page 2 for technical characteristics

## P/N MS16997-19L Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.280 Inches Minimum And 0.375 Inches Maximum
<b>Fastener Length:</b>	0.342 Inches Minimum And 0.375 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.218 Inches Minimum And 0.226 Inches Maximum
<b>Head Height:</b>	0.134 Inches Minimum And 0.138 Inches Maximum
<b>Locking Feature:</b>	Patch Threads Or Strip Threads
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Width Across Flats:</b>	0.109 Inches Minimum And 0.111 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	38.0 Rockwell C Minimum Fastener And 45.0 Rockwell C Maximum Fastener
<b>Material:</b>	Plastic Locking Feature
<b>Material:</b>	Steel Fastener
<b>Material Document And Classification:</b>	Mil-f-18240 Mil Spec Single Material Response Locking Feature
<b>Surface Treatment:</b>	Cadmium Fastener And Chromate Fastener
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Fastener
<b>Thread Series Designator:</b>	Unc
<b>Nondefinitive Spec/std Data:</b>	4 Type

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS16997-19L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.