

## P/N MS16997-2

### **Description**

Fastener Length: 1/4", Thread: 2-56, Head Width: 5/64", Thread Length: 7/32",

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

#### **Alternate Part Numbers**

NAS1352-02-4P

SKU / Model: MS169972

Minimum Qty (MOQ): 50

NSN: 5305-00-952-8492

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N MS16997-2 Specifications

| Thread Class:                                  | 3a                                                                  |
|------------------------------------------------|---------------------------------------------------------------------|
| Thread Direction:                              | Right-hand                                                          |
| Thread Length:                                 | 0.230 Inches Minimum                                                |
| Fastener Length:                               | 0.250 Inches Nominal                                                |
| Head Style:                                    | Flat Chamfer                                                        |
| Head Diameter:                                 | 0.134 Inches Minimum And 0.140 Inches Maximum                       |
| Head Height:                                   | 0.083 Inches Minimum And 0.086 Inches Maximum                       |
| Internal Drive Style:                          | Hexagon                                                             |
| Nominal Thread Diameter:                       | 0.086 Inches                                                        |
| Width Across Flats:                            | 0.078 Inches Minimum And 0.079 Inches Maximum                       |
| Thread Quantity Per Inch:                      | 56                                                                  |
| Minimum Tensile Strength:                      | 160000 Pounds Per Square Inch                                       |
| Hardness Rating:                               | 36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall |
| Minimum Yield Strength:                        | 130000 Pounds Per Square Inch                                       |
| Material:                                      | Steel Overall                                                       |
| Material Document And Classification:          | 66 Fed Std Single Material Response Overall                         |
| Surface Treatment:                             | Cadmium Overall And Chromate Overall                                |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall         |
| Thread Series Designator:                      | Unc                                                                 |

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS16997-2">https://military-fasteners.com/screws/machine+screws/MS16997-2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.