

Description

Fastener Length: 1-63/64", Thread: 1--8, Head Width: 3/4", Thread Length: 1-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS16997228
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-978-9363
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS16997-228 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.650 Inches Minimum And 2.000 Inches Maximum
Fastener Length:	1.900 Inches Minimum And 2.000 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	1.479 Inches Minimum And 1.500 Inches Maximum
Head Height:	0.988 Inches Minimum And 1.000 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	1.000 Inches
Width Across Flats:	0.750 Inches Minimum And 0.757 Inches Maximum
Thread Quantity Per Inch:	8
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	130000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	6 Type

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS16997-228> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.