

Description

Fastener Length: 3/4", Thread: 6-32, Head Width: 7/64", Thread Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS1699722L
Minimum Qty (MOQ):	40 EA
NSN:	5305-01-273-6241
Schedule B:	7318.15.2010
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N MS16997-22L Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.657 Inches Minimum And 0.750 Inches Maximum
Fastener Length:	0.719 Inches Minimum And 0.750 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.218 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.134 Inches Minimum And 0.138 Inches Maximum
Locking Feature:	Pellet Locking Feature Or Strip Locking Feature
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.109 Inches Minimum And 0.111 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Fastener And 45.0 Rockwell C Maximum Fastener
Minimum Yield Strength:	155000 Pounds Per Square Inch
Material:	Plastic Locking Feature
Material:	Steel Fastener
Surface Treatment:	Cadmium Fastener And Chromate Fastener
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Fastener
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS16997-22L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.