

P/N MS16997-4

Description

Fastener Length: 1/2", Thread: 2-56, Head Width: 5/64", Thread Length: 1/2", MS16997 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS169974

Minimum Qty (MOQ): 10

NSN: 5305-00-058-2076

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS16997-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.433 Inches Minimum And 0.500 Inches Maximum
Fastener Length:	0.469 Inches Minimum And 0.500 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.134 Inches Minimum And 0.140 Inches Maximum
Head Height:	0.083 Inches Minimum And 0.086 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.086 Inches
Width Across Flats:	0.078 Inches Minimum And 0.079 Inches Maximum
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	130000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	6 Type

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/MS16997-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.