

Description

Fastener Length: 63/64", Thread: 10-24, Head Width: 5/32", Thread Length: 0-63/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS1699748
Minimum Qty (MOQ):	20
NSN:	5305-00-978-9358
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS16997-48 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.886 Inches Minimum And 1.000 Inches Maximum
Fastener Length:	0.969 Inches Minimum And 1.000 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.303 Inches Minimum And 0.313 Inches Maximum
Head Height:	0.185 Inches Minimum And 0.190 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.156 Inches Minimum And 0.159 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	130000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	6 Type

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS16997-48> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.