

## P/N MS16998-102

## **Description**

Fastener Length: 2-59/64", Thread: 1/2-20, Head Width: 3/8", Thread Length: 1-27/64",

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS16998102

Minimum Qty (MOQ): 2

NSN: 5305-00-983-8076

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N MS16998-102 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.420 Inches Minimum And 1.885 Inches Maximum
Fastener Length:	2.920 Inches Minimum And 3.000 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.735 Inches Minimum And 0.750 Inches Maximum
Head Height:	0.492 Inches Minimum And 0.500 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.500 Inches
Width Across Flats:	0.375 Inches Minimum And 0.379 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	130000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Ams-qq-p-416, Ty 2, Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	6 Type

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS16998-102">https://military-fasteners.com/screws/machine+screws/MS16998-102</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.