

Description

Fastener Length: 2-59/64", Thread: 1/2-20, Head Width: 3/8", Thread Length: 1-27/64",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS16998102 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 5305-00-983-8076 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS16998-102 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.420 Inches Minimum And 1.885 Inches Maximum |
| Fastener Length: | 2.920 Inches Minimum And 3.000 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.735 Inches Minimum And 0.750 Inches Maximum |
| Head Height: | 0.492 Inches Minimum And 0.500 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.500 Inches |
| Width Across Flats: | 0.375 Inches Minimum And 0.379 Inches Maximum |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall |
| Minimum Yield Strength: | 130000 Pounds Per Square Inch |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Ams-qq-p-416, Ty 2, Cl 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unf |
| Nondefinitive Spec/std Data: | 6 Type |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS16998-102> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.